



# Best in class Extruded Aluminium batten with high Lumen Efficacy. Sleek but robust design

## Smartbright BN100 Batten

High performance LED batten, can replace 2x40W conventional batten suitable for Classroom, hostel room, corridor, small shops, community center, club, small warehouse lighting applications.

### Benefits

- Long Useful life
- Volumetric distribution improving safety in industrial environment
- Sleek aesthetic design complements interiors

### Features

- Suitable for Surface & suspension mounting
- Extruded aluminium housing
- Slim integrated design, easy to install
- Energy Saving of up to 60% compared to conventional lighting

### Application

- General Indoor Lighting
- Industrial usage

### Warnings and Safety

- Meant for use in Indoor environment only

# Smartbright BN100 Batten

## Versions



### Application Conditions

Ambient temperature range	0 to +45 °C
---------------------------	-------------

### Approval and Application

Mech. impact protection code	IK02
------------------------------	------

Ingress protection code	IP20
-------------------------	------

### Controls and Dimming

Dimmable	No
----------	----

### Operating and Electrical

Input Voltage	220-240 V
---------------	-----------

### General Information

Protection class IEC	Safety class II (II)
----------------------	----------------------

Driver included	Yes
-----------------	-----

### Initial Performance (IEC Compliant)

Init. Color Rendering Index	>80
-----------------------------	-----

### Mechanical and Housing

Color	Aluminum and gray
-------	-------------------

### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Init. Corr. Color Temperature	Initial input power
919515811980	BN100C LED40S-6500 PSU L120 GR	6500 K	40 W
919515811981	BN100C LED40S-4000 PSU L120 GR	4000 K	41 W

