



Philips MASTER LEDtube 30W 4000lm Mains T8



PHILIPS

MASTER LEDtube 30W 4000lm Mains T8



4000lm, > 130lumen/W

New Master HO ``High Output``

The MASTER LEDtube HO ``High Output`` T8, has been designed for the world's best-in-class lumen performance of >130 lm/W. With a long lifetime of 40,000 hours, these lamps offer a high lumen output of 4000 lm along with the best Total Cost of Ownership over lifetime. Ideal for demanding applications with very long burning hour periods, such as industrial, retail, office and healthcare applications, they're compatible for use with mains power

Product benefits

- Ultra High Output, High performance, low energy consumption
- Best Total Cost Of Ownership & Payback for all applications
- Plastic all around design with Al heatsink for lifetime product reliability
- Compatible with Direct mains
- Negligible/minimized downtime with easy replacement
- Available in 1200mm versions

Applications

The ideal solution for demanding applications combined with high energy saving requirements: industry, textiles, car parks, retail, hospitals, govt .offices, public areas, schools, etc



MASTER LEDtube 30W 4000lm Mains T8



4000lm, >130lumen/W

Technical Specifications And Ordering Details

Technical Specifications	
Commercial type	Master LEDtube 1200mm 30W 865 T8
Application	General Lighting Office & Industrial
Rated Power (typical)	30W±10%
Rated Voltage (Performance)	220 ~ 240Vac
Rated Voltage (Operational)	140 ~ 280Vac
Rated Frequency (range)	50Hz
Rated Current (typical)	130mA±10%
Power factor (min.)	0.9
Surge Protection	3 KV
THDi	<15%
Rated Lumen (typical)	4000lm
Luminous Efficacy(typical)	130 Lm/w
Lamp Base	G13
Lamp Type (size)	T8/4ft/Standard
Rated CCT	6500K
Consistency	ANSI
Rated CRI (Min)	80
Beam angle	150°
Operating Temperature range	-20 ~ 45°C
Mechanical Platform	PC Tube with Internal Heatsink
Weight (max)	500g
Rated Lifetime (L70F50) @25°C free air	40,000Hrs
Dimmability	Non-dimmable
Ingress Protection	IP-20
Transformer Compatibility	Mains only
Starting time	<=0.5s

Product Image	12nc	Material description	Wattage (W)	CCT (K)	MRP (INR)
	929002030114	MAS LEDTube 30w,4000lm,865 T8	30	6500	1499
	929002030115	MAS LEDTube 30w, 4000lm (with batten)	30	6500	1699



 Signify

MASTER LEDtube 30W 4000lm Mains T8



4000lm, >130lumen/W

Application Areas/Target Customers



Industry



Retail



Textiles



Public Areas



Hospitals



Schools



Warehouses



Textiles/ Spinning Mills

Warehouses

Govt Buildings - CPWD/Railways/MES

Super Markets/Hyper Markets/ Other Retail Formats

Industries – Automobile/ Manufacturing

Warehousing

Hospitals

Public Areas



Signify